

Carboflex ® / EN Oil and petrol resistant suction/discharge tanker truck hose



Technical specifications:

It's persistent against mineral oil products, up to max 50% aroma content.

Felirat: ® CARBOFLEX® - MANUFACTURERS NAME EN 12115:2011 NBR-1 - SD - PN.. - WP 16 BAR - Q/T - TRBF 131/T2 P5.5 - QUARTER/YEAR

Operating pressure: 16 bar

Bursting pressure: 64 bar

Heat resistance: -30°C/+90°C

Interior: NBR? Black, smooth

Exterior: CR, black, fabric imprinted

Linings: steel wire helix

Vacuum: -0,9 bar

Electrical resistance: < 106 Ω

Átmenő ellenállás: < 109 Ω

Standard: EN 12115:2011 and TRbF131 part 2. 5.5 §

Storage lots, splitting of the rolls are possible. Meantime, we hold the right of selling the stock in products.

Belső Ø (mm)	Falvastagság (mm)	Külső Ø (mm)	Tekercsméret (m)	Cikkszám
25	6	37	40	3356 025000
32	6	44	40	3356 032000
38	6,5	51	40	3356 038000
50	8	66	40	3356 050000
63,5	8	79,5	40	3356 063000
75	8	91	40	3356 075000
100	8	116	40	3356 100000