

Corrosiv / SP /EN Acid and alkali suction/discharge hose of the chemical industry



Technical specifications:

It is suitable for strong acids and alkalis. It does not persist against hydrocarbons. The hose can be steamed, for short time even with high temperature, up to 120°C.

Felirat: ® CORROSIV® CHEMHOSE / CHEMIESCHLAUCH** EN 12115
EPDM - SD - ID MM - WP 16 BAR Q/T TRBF 131/T2 P.5.5 QUARTER/YEAR

Operating pressure: 16 bar

Bursting pressure: 64 bar

Heat resistance: -35°C/+95°C(depending on the medium)

Interior: EPDM, black, smooth

Exterior: EPDM, black, fabric imprinted

Linings: steel spiral spiral

Vacuum: -0,9 bar

Bending radius: 8 x inside Ø

Standard: EN 12115and TRbF131 part 2. 5.5 §

Storage lots, splitting of the rolls are possible. Meantime, we hold the right of selling the stock in products.

Inside Ø (mm)	Wall thickness (mm)	Outside Ø (mm)	Roll size (m)	Article number
25	6	37	40	3830 025000
32	6	44	40	3830 032000
38	6,5	51	40	3830 038000
50	8	66	40	3830 050000
63,5	8	79,5	40	3830 063000
75	8	91	40	3830 075000
100	8	116	40	3830 100000