

## CORRUFLEX/BUNA/AS Water suction, oil resistant, ultra flexible hose, new development



### Technical specifications:

The hose is made of quality materials, which is a newly developed PVC/NBR mixture. It is really flexible, even in cold, and can be grounded. The hose is recommended for water, sewage, oily water, fertilizer and medium or heavy-duty.

**Heat resistance:** -30°C / +65°C

**Structure:** black, blue spirak

**Interior:** black, smooth

**Exterior:** corrugated, blue spiral

**Vacuum:** -0,9 bar

**Material:** PVC/NBR mix

**Bending radius:** 3 x inside Ø

Storage lots, splitting of the rolls are possible. Meantime, we hold the right of selling the stock in products.

### CORRUFLEX/BUNA/AS A spirállal együtt futó rézszállal, mely által a tömlő leföldelhető

| Inside Ø<br>(mm) | Outside Ø<br>(mm) | Operating pressure<br>(bar) | Weight<br>(kg/m) | Wall thickness<br>(mm) | Roll size<br>(mm) | Article<br>number |
|------------------|-------------------|-----------------------------|------------------|------------------------|-------------------|-------------------|
| 51               | 60                | 2                           | 0,96             | 4,5                    | 50                | 4466 050000       |
| 76               | 87                | 2                           | 1,6              | 5,5                    | 50                | 4466 075000       |
| 102              | 116               | 2                           | 2,7              | 7                      | 50                | 4466 100000       |
| 127              | 142               | 2                           | 3,27             | 7,5                    | 20                | 4466 125000       |
| 152              | 168               | 2                           | 4,6              | 8                      | 20                | 4466 150000       |



TRIÁSZ-TÖMLŐ KFT.

