

FEP-Fluorperform EN 12115-FDA rubber chemical hose with FEP insertion



Technical specifications:

The hose has a chemical resistance similar to Teflon. It is antistatic and solvent resistant. The interior quality is high purity according to the FDA. The suction, discharge hose is steel reinforced with fabric insertion (it is also called rubber hose with Teflon insertion).

Operating pressure: 16 bar

Bursting pressure: 64 bar

Heat resistance: according to EN12115:2011 , alsp -30°C / +110°C depending on the transfered medium, for short time 130°C in case of sterilization max. 30 minutes

Interior: FEP (Fluorinated Ethylene Propylene) coating, light coloured, smooth, FDA quality

Exterior: black, electrically conductive rubber, abrasion and weather resistant, fabric imprinted

Linings: fabric linings, steel wire helix for grounding

Roll size: 20 m

Vacuum: -0,9 bar

Electrical resistance: $10^6 \Omega$

Storage lots, splitting of the rolls are possible. Meantime, we hold the right of selling the stock in products.

Inside Ø (mm)	Outside Ø (mm)	Bending radius (mm)	Weight (kg/m)	Article number
13	25	78	0,5	230045
19	31	125	0,75	230046
25	37	150	0,94	230047
32	44	175	1,1	230048
38	51	225	1,5	230049
51	65,5	275	2,4	230050
63,5	79,5	300	2,95	230051
76	92	350	3,6	230052