

Kehrflex Street vacuum cleaner hose with steel wire helix



Technical specifications:

It is an abrasive resistant, inside and outside corrugated hose with a green natural caoutchouc interior. The cover is a weather resistant, anti-static, corrugated NR material. The hose is longitudinal slightly compressible, flexible.

Both end has a +/-100 mm long spiral free cuff. Special convoluted hose in street sweeping machines for suction of leaves, grass and general debris

Inside: Green, corrugated, abrasion resistant, NR – Naturkauchuk

Abrasion value Inside according DIN 53516: 250 mm³

Temperature: -30/+85 C

Outside: NR, black, corrugated, cloth impression, antistatic, resistant to weather, ozone and abrasion

Abrasion value outside according DIN 53516: 60 mm³

Ends: Both ends with soft cuffs

Electrical conductivity cover: R<10 6 Ω/m

Just for order!

Inner diameter (mm)	Outer diameter (mm)	Wall thickness (mm)	Max. Vacuum (bar)	Bending radius mm	Weight kg/m	Possible length m	Article Nr. (* means the length)
120	130	5	-0,4	240	3,8	4,5	3612 120450
152	162	5	-0,4	304	4,32	1,47-2	3612 152***
200	210	5	-0,4	400	6,01	0,6	3612 200060
203	213	5	-0,4	406	6,51	0,48-4	3612 203***
210	220	5	-0,3	420	6,7	1,85	3612 210185
220	230	5	-0,3	440	6,95	0,75-1,9	3612 220***
220	232	6	-0,3	440	6,95	1,47-2	3613 220***
225	235	5	-0,3	450	7,08	0,86	3612 225086
230	240	5	-0,3	460	6,32	0,87-1,5	3612 230***
254	264	5	-0,3	508	8,65	0,55-8	3612 254***
254	270	8	-0,3	508	9,41	6	3613 254600
280	290	5	-0,2	560	7,15	1,48	3612 280148
300	310	5	-0,2	600	8,53	1,5-2	3612 300***
300	314	7	-0,2	600	9,54	1,2-1,75	3613 300***
350	360	5	-0,2	700	10,16	0,74	3612 350074
400	415	7,5	-0,2	800	16,71	3,6	3612 400360



TRIÁSZ-TÖMLŐ KFT.

