

Metalvapor EN/ISO Steam hose with steel insertion



Technical specifications:

The steam hose with steel insertion is suitable for hot water, saturated steam. It has a good resistance against acids and alkalis. After use, the water has to be let down from the hose.

The use of the overheated steam causes premature ageing.

Standard: MSZ EN ISO 6134:2005 Type 2 Class A

Felirat: ® METALVAPOR® - MANUFACTURER - EN/ISO 6134: 2005 - 2A-STEAM - SIZE- WP 18 BAR - BP 180 BAR - Ω - QUARTER / YEAR LOTNR

Üzemi nyomás: 18 bar (telített gőzre) 55 bar (forró vízre)

Repesztési nyomás: 180 bar 20°C-on

Hőállóság: -35°C / maximum +210 °C, vízre +120 C-ig

Belül: EPDM, fekete, sima, vezetőképés

Kívül: EPDM, fekete, szövetlenyomatos, vezetőképés, „pin-pricked”

Betétek: kettős, szövött acélszövetbetét

Eletromos ellenállás: < 10 6 Ω

Szabvány: EN/ISO 6134 Type 2/A

Storage lots, splitting of the rolls are possible. Meantime, we hold the right of selling the stock in products.

Belső Ø (mm)	Falvastagság (mm)	Külső Ø (mm)	Tekercsméret (m)	Cikkszám
13	6	25	40	3411 013000
19	7	33	15	3411 019015
19	7	33	20	3411 019020
19	7	33	40	3411 019000
25	7,5	40	20	3411 025020
25	7,5	40	40	3411 025000
32	8	48	40	3411 032000
38	8	54	40	3411 038000
51	9	69	40	3411 050000