

## Naftoil / Buna PVC/NBR suction/discharge hose



### Technical specifications:

It's suitable for service and mineral water, even with difficult working environment.

**It's really flexible, even in cold weather.**

**Bending radius: inside diameter x 3 !!**

**Felirat:** ® NAFTOIL / BUNA - Ø SIZE- PROD. CODE

**Heat resistance:** -30°C/+65°C

**Structure:** PVC/NBR mix, gray, embedded PVC spiral

**Vacuum:** -0,9 bar

Certain diameters are available from stock. Meantime, we hold the right of selling the stock in products.

| Inside Ø (mm) | Wall thickness (mm) | Outside Ø (mm) | Pressure on 20°C (bar) | Weight (kg/m) | Roll size (m) | Article number |
|---------------|---------------------|----------------|------------------------|---------------|---------------|----------------|
| 25            | 4                   | 33             | 7                      | 0,44          | 50            | 4465 025000    |
| 32            | 4,5                 | 41             | 6                      | 0,6           | 50            | 4465 032000    |
| 38            | 5                   | 48             | 6                      | 0,7           | 50            | 4465 038000    |
| 51            | 5                   | 61             | 5                      | 0,98          | 50            | 4465 050000    |
| 63            | 5,5                 | 74             | 4,5                    | 1,2           | 50            | 4465 063000    |
| 76            | 6                   | 88             | 4                      | 1,6           | 50            | 4465 075000    |
| 80            | 6                   | 92             | 3                      | 1,7           | 50            | 4465 080000    |
| 90            | 7                   | 104            | 3                      | 2,2           | 50            | 4465 090000    |
| 102           | 7                   | 116            | 3                      | 2,4           | 50            | 4465 100000    |
| 127           | 8                   | 143            | 2                      | 3,3           | 20            | 4465 125000    |
| 152           | 8,5                 | 169            | 2                      | 4,2           | 20            | 4465 150000    |