

PTFE corrugated metal braided Corrugated teflon hydraulic hose with metal braiding



Technical specifications:

It is suitable for the high pressure flow off paint, oil, air, water based liquids and unsaturated steam.

We can deliver to you the hoses assembled with couplings.

Temperature: -60°C / +260°C

Inside: PTFE Corrugated ASTM D4895,TYPE 1, GRADE4, CLASS B

Outside: AISI 304 stainless steel braiding

Storage lots, splitting of the rolls are possible. Meantime, we hold the right of selling the stock in products.

PTFE corrugated teflon hydraulic hose

DN	Inside diameter (mm)	Wall thickness (mm)	Outer diameter (mm)	Diameter tolerance (mm)	Working / Burst pressure on 20 °C (bar)	Bending radius (mm)	Article Number
10	9,5	0,76	14,75	0,6	138/414	20	200110
13	12,83	0,89	18,8	0,6	103/310	25	200010
16	15,88	0,89	22,1	0,6	83/248	51	200020
19	19,05	0,89	24,65	0,7	69/207	64	200030
25	25,4	1,02	32,77	0,8	46/138	89	200040
32	32,2	1,02	40,72	0,8	34/103	127	200457
38	38,1	1,12	47	0,8	30/90	152	200450
50	51,4	1,1	60	0,8	23/69	200	200165