

Turboflex / U.L. / OHM Conductive, abrasion resistant rubber suction hose, lightweight and flexible



Technical specifications:

The abrasion resistant rubber hose is suitable for pebbles, tailings and other abrasive medium. It is extremely flexible, lightweight and easy to handle.

Felirat: ® TURBOFLEX/UL/OHM - SAUG/DRUCK - SUCTION/DISCHARGE - ABRIEB/ABRASION 60 MM3 - WP 5 BAR - BP 15 BAR - Ω

Operating pressure: 5 bar

Bursting pressure: 15 bar

Heat resistance: -25°C / +80°C

Interior: NR6SBR, black, smooth, abrasion-resistant, electrically conductive

Exterior: SBR, black, fabric imprinted, corrugated, antistatic

Linings: steel wire helix

Roll size: 20 m

Vacuum: -0,9 bar

Electrical resistance: < 10⁶ Ohm

Abrasion value: 60 mm³ according to ISO 4649 (earlier DIN 53516)

Bending radius: 2,5 x inside ø

Storage lots, splitting of the rolls are possible. Meantime, we hold the right of selling the stock in products.

Belső Ø (mm)	Falvastagság (mm)	Külső Ø (mm)	Súly (kg/m)	Hajlítási sugár (mm)	Tekercsméret (m)	Cikkszám
51	5,5	62	1,31	130	20	3508 050000
63	6	75	1,8	160	20	3508 063000
76	6	88	2,13	190	20	3508 075000
102	6,5	115	3,07	255	20	3508 100000
127	8,5	144	5,11	380	20	3508 125000
152	8,5	169	6,04	460	20	3508 150000