

# Vacuum quick coupling For suction/discharge hose



**Technical specifications:**

The male and female stainless steel quick coupling is suitable for abrasive material delivering such as granulate, but it also works with liquids and other wet or pulverized medium.

It's lightweight and easy to handle with a large flow diameter. It applies well with lightweight spiral hoses.

available design:with hose tail, male thread and for rigid (plastic) tube (e.g. suction granulate), fix with a screw from the outside

Material:

The coupling's body is stainless steel 1.4305

The blind plug and cap are aluminium

The spring, balls, chain, and screws are stainless steel 1.4410

Sealing: Buna-N

**Operating pressure:** 10 bar

**HEat resistance:** -15/+95 C

**Vacuum:** suitable for vacuum

Certain diameters are available from stock. Meantime, we hold the right of selling the stock in products.

|                                            | Male part         | Female part       |
|--------------------------------------------|-------------------|-------------------|
| Female thread (coll)                       | 1.1/2" - 2"       | 1.1/2" - 2"       |
| Hose inside diameter (mm)                  | 38 - 40 - 45 - 50 | 38 - 40 - 45 - 50 |
| Outside diameter to put it on a rigid tube | 38 - 40 - 45 - 50 | 38 - 40 - 45 - 50 |
| Closure                                    | Vakdugó           | Zárósapka         |