

Vaporcord Steam hose with fabric insertion



Technical specifications:

The steam hose with fabric insertion is suitable for hot water and saturated steam.

After use, the steam water has to be let down from the hose. The use of the overheated steam causes premature ageing.

Felirat: ® VAPORCORD® STEAMHOSE / DAMPFSCHLAUCH PN 7 BAR - MAX. 164°C - HOT WATER/HEISSWASSER PN 20 BAR MAX. +95°C

Operating pressure: 7 bar for saturated steam on 160°C , 20 bar for hot water

Bursting pressure: 70 bar

Heat resistance: -40°C/ +164°C for saturated steam, +95 °C for hot water

Interior: EPDM, black, smooth

Exterior: EPDM, black, fabric imprinted

Lining: fabric linings

Storage lots, splitting of the rolls are possible. Meantime, we hold the right of selling the stock in products.

Inside Ø (mm)	Wall thickness (mm)	Outside Ø (mm)	Roll size Ø (mm)	Article number
10	5,5	21	40	3400 010000
13	5,5	24	40	3400 013000
19	7	33	40	3400 019000
25	7	39	40	3400 025000
32	7,5	47	40	3400 032000
38	9	56	40	3400 038000
51	9	69	40	3400 050000
63,5	10	83,5	40	3400 063000
76	11	98	40	3400 075000